

Technical Specification

Product Code: VPMB750BK

Description: 13A Ingot Fused Connection Unit



General Information

| | | |
|--|---|---|
| Plate Dimensions (mm) | 88 (W) x 88 (H) x 8 (D) | |
| Dimensions With Gasket (mm) | 91 (W) x 91 (H) x 9 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Victorian | |
| Finish | Matt Black | |
| Insert Colour | Black | |
| Gasket Colour | Black | |
| Materials | Front Plate: Stainless Steel Fuse Drawer Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel | Insert & Housing: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass Gasket: Nylon |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 13 | |
| Fuse Fitted Rating & Type | 13A (BS 1362) | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 2 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 | |
| Switched | No | |
| Twin Earth Terminals | Yes | |
| Product Marking | Fused | |
| Minimum Back Box Depth (mm) | 25 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |
| Standards | BS 1363-4 BS 1362 | |

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Supplied with Matt Black plate fixing screws.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.