


## DATASHEET



### TPR14LED

230V IP65 14W LED Bulkhead 4000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	TPR14LED
DESCRIPTION	230V IP65 14W LED Bulkhead 4000K
NET WEIGHT (KG)	0.55
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 285 Projection - 86
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1100
LUMENS LIGHT SOURCE ONLY (LM)	1475
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	105.4
CIRCUIT WATTAGE (W)	14
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.027
BEAM ANGLE (DEGREES)	115
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	60,000

<b>DIMMABLE</b>	No
<b>OPERATING TEMPERATURE</b>	-20~50°C
<b>INPUT VOLTAGE</b>	230V 50Hz
<b>CABLE ENTRY (MM)</b>	20
<b>CABLE GLAND INCLUDED</b>	Blind grommet
<b>DRIVER</b>	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 83.6 CASE TEMPERATURE (Tc) - 50°C
<b>WARRANTY</b>	3year(s)
<b>MANUFACTURED IN ACCORDANCE WITH</b>	BS EN 60598
<b>ORIGIN OF MANUFACTURE</b>	China
<b>DECLARATION OF CONFORMITY (HELD ON FILE)</b>	Yes
<b>EAN</b>	5055832936930

Date Created: 19/08/2022 14:35

