

Soudal DE-ICER

Revision: 14/12/2022

Page 1 from 1

Technical data

| | |
|----------------------------------|----------------------|
| Basis | Solventbased mixture |
| Consistency | Liquid |
| Density | 0,81 g/ml |
| Solubility in water | Fully soluble |
| Volatile Organic Compounds (VOC) | 96 % |
| Application temperature | -20 °C → 30 °C |

Product description

Quickly defrosts ice and snow (up to -20° Celsius) on your windshield and other windows, without leaving a trace.

Properties

- Fast action
- Leaves no residue
- Works well with a thick layer of frost

Applications

- All glassware
- Locks

Packaging

Colour: Transparent

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Glass and metal

Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. Wipe the windshield with a cloth after applying the product. Avoid contact with the bodywork. When the aerosol is kept for a long time below 5°C, there is a risk the yield of the aerosol drops. When this is the case, bring the aerosol back on the recommended temperature between 5 - 25°C (never use direct heating).

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. The products mentioned in Annex II of Regulation (EU) 1169/2011 are not part of our formulations and to the best of our knowledge our products do not contain these ingredients.

Dangerous. Respect the precautions for use.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.