

## Soudal high viscosity super glue

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Soudal high viscosity super glue  
 Registration number REACH : Not applicable (mixture)  
 Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Adhesive

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

SODAL N.V.  
 Everdongenlaan 18-20  
 B-2300 Turnhout  
 ☎ +32 14 42 42 31  
 ☐ +32 14 42 65 14  
 msds@soudal.com

##### Manufacturer of the product

SODAL N.V.  
 Everdongenlaan 18-20  
 B-2300 Turnhout  
 ☎ +32 14 42 42 31  
 ☐ +32 14 42 65 14  
 msds@soudal.com

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):  
 +32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.

#### 2.2. Label elements



##### Signal word

##### H-statements

H319  
 H335  
 H315

##### P-statements

P101  
 P102  
 P280  
 P304 + P340  
 P302 + P352  
 P362 + P364

##### Warning

Causes serious eye irritation.  
 May cause respiratory irritation.  
 Causes skin irritation.

If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Wear protective gloves, protective clothing and eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF ON SKIN: Wash with plenty of water and soap.  
 Take off contaminated clothing and wash it before reuse.

# Soudal high viscosity super glue

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulation.  
**Supplemental information**  
EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

## 2.3. Other hazards

Warning! Product may cause floors to be slippery

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
ethyl 2-cyanoacrylate	7085-85-0 230-391-5	C>25 %	Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315	(1)(2)(8)(10)	Constituent
6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol 01-2119496065-33	119-47-1 204-327-1	0.1%<C<1%	Repr. 2; H361f	(1)	Constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(8) Specific concentration limits, see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

#### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

#### After skin contact:

Do not pull surfaces apart with a direct opposing action. Immerse the bonded surfaces in warm, soapy water. Peel or roll surfaces apart with a blunt edge, e.g. spatula. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.

#### After eye contact:

Do not try to open the eyes by manipulation. Wash thoroughly with warm water. Apply a moist gauze patch. Take victim to an ophthalmologist.

#### After ingestion:

Do not try to pull the lips with a direct opposing action. Apply lots of warm water and saliva. Consult a doctor/medical service if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Dry/sore throat. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Coughing. EXPOSURE TO HIGH CONCENTRATIONS: Respiratory difficulties.

##### After skin contact:

Red skin. Tingling/irritation of the skin.

##### After eye contact:

Irritation of the eye tissue.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

2 / 13

# Soudal high viscosity super glue

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Water spray. BC powder. Carbon dioxide. Polyvalent foam.

#### 5.1.2 Unsuitable extinguishing media:

Solid water jet ineffective as extinguishing medium.

### 5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide).

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves. Face-shield. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

#### 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves. Face-shield. Protective clothing.

#### Suitable protective clothing

See heading 8.2

### 6.2. Environmental precautions

Contain released product. Use appropriate containment to avoid environmental contamination.

### 6.3. Methods and material for containment and cleaning up

Liquid spill: allow to react with an excess of water. Allow product to solidify and remove it by mechanical means. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Keep away from naked flames/heat. Gas/vapour heavier than air at 20°C. Observe strict hygiene. Keep container tightly closed. Remove contaminated clothing immediately.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: 2 °C - 8 °C. Store in a cool area. Store in a dry area. Ventilation at floor level. Keep out of direct sunlight. Keep only in the original container. Meet the legal requirements. Max. storage time: 1 year(s).

#### 7.2.2 Keep away from:

Heat sources, oxidizing agents, (strong) bases, (strong) acids, alcohols, amines, water/moisture.

#### 7.2.3 Suitable packaging material:

Polyethylene.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### Belgium

2-Cyanoacrylate d'éthyle	Time-weighted average exposure limit 8 h	0.2 ppm
	Time-weighted average exposure limit 8 h	1.04 mg/m <sup>3</sup>

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

3 / 13

# Soudal high viscosity super glue

## The Netherlands

Ethyl(2-)cyanoacrylaat	Short time value (Private occupational exposure limit value)	0.29 ppm
	Short time value (Private occupational exposure limit value)	1.5 mg/m <sup>3</sup>

## UK

Ethyl cyanoacrylate	Short time value (Workplace exposure limit (EH40/2005))	0.3 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1.5 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Ethyl cyanoacrylate	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	0.2 ppm
---------------------	--	---------

### b) National biological limit values

If limit values are applicable and available these will be listed below.

### 8.1.2 Sampling methods

If applicable and available it will be listed below.

Ethyl 2-Cyanoacrylate	OSHA	55
-----------------------	------	----

### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 DNEL/PNEC values

#### DNEL/DMEL - Workers

##### ethyl 2-cyanoacrylate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	9.25 mg/m <sup>3</sup>	
	Long-term systemic effects inhalation	9.25 mg/m <sup>3</sup>	

##### 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	4.48 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	22.4 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.635 mg/kg bw/day	
	Acute systemic effects dermal	3.175 mg/kg bw/day	

#### DNEL/DMEL - General population

##### ethyl 2-cyanoacrylate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	9.25 mg/m <sup>3</sup>	
	Long-term systemic effects inhalation	9.25 mg/m <sup>3</sup>	

##### 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1.1 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	5.5 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	0.318 mg/kg bw/day	
	Acute systemic effects dermal	1.59 mg/kg bw/day	
	Long-term systemic effects oral	0.318 mg/kg bw/day	
	Acute systemic effects oral	1.59 mg/kg bw/day	

#### PNEC

##### 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol

Compartments	Value	Remark
Oral	10 mg/kg food	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe strict hygiene. Keep container tightly closed. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

#### b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
nitrile rubber	> 30 minutes	>0.4 mm

- materials (good resistance)

Nitrile rubber.

#### c) Eye protection:

Face shield.

#### d) Skin protection:

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

4 / 13

# Soudal high viscosity super glue

Protective clothing.

## 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Irritating/pungent odour
Odour threshold	No data available
Colour	Colourless
Particle size	Not applicable
Explosion limits	No data available
Flammability	Material presenting a fire hazard
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	> 149 °C
Flash point	80 °C - 93 °C
Evaporation rate	No data available
Relative vapour density	> 2
Vapour pressure	< 700 hPa ; 50 °C
Solubility	water ; reacts
Relative density	1.05
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

### 9.2. Other information

Absolute density	1050 kg/m <sup>3</sup>
------------------	------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

### 10.2. Chemical stability

Unstable on exposure to moisture.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Keep away from naked flames/heat.

### 10.5. Incompatible materials

Oxidizing agents, (strong) bases, (strong) acids, alcohols, amines, water/moisture.

### 10.6. Hazardous decomposition products

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### 11.1.1 Test results

#### Acute toxicity

#### Soudal high viscosity super glue

No (test) data on the mixture available

#### ethyl 2-cyanoacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male)	Experimental value	
Skin	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male)	Experimental value	

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

5 / 13

# Soudal high viscosity super glue

## 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 10000 mg/kg bw		Rat (male)	Experimental value	
Dermal	LD50		> 10000 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation						Data waiving	

Judgement is based on the relevant ingredients

### Conclusion

Not classified for acute toxicity

### Corrosion/irritation

#### Soudal high viscosity super glue

No (test) data on the mixture available

#### ethyl 2-cyanoacrylate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Slightly irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Experimental value	
Inhalation	Irritating; STOT SE cat.3					Literature study	

## 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

Classification is based on the relevant ingredients

### Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

### Respiratory or skin sensitisation

#### Soudal high viscosity super glue

No (test) data on the mixture available

#### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value	

Judgement is based on the relevant ingredients

### Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

### Specific target organ toxicity

#### Soudal high viscosity super glue

No (test) data on the mixture available

#### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL		12.7 mg/kg bw/day	Liver	No effect	18 month(s)	Rat (male)	Experimental value
Oral (diet)	LOAEL		42.3 mg/kg bw/day	Liver; testes	Enlargement/affection of the liver	18 month(s)	Rat (male)	Experimental value
Oral (diet)	NOAEL		15.1 mg/kg bw/day	Liver; testes	No effect	18 month(s)	Rat (female)	Experimental value
Oral (diet)	LOAEL		54.2 mg/kg bw/day	Liver	Enlargement/affection of the liver	18 month(s)	Rat (female)	Experimental value
Dermal								Data waiving
Inhalation								Data waiving

Judgement is based on the relevant ingredients

### Conclusion

Not classified for subchronic toxicity

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

6 / 13

# Soudal high viscosity super glue

## Mutagenicity (in vitro)

### Soudal high viscosity super glue

No (test)data on the mixture available

### ethyl 2-cyanoacrylate

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 473	Human lymphocytes	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value

### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 476	Chinese hamster lung fibroblasts (V79)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	OECD 473	CHL/IU cells	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

## Mutagenicity (in vivo)

### Soudal high viscosity super glue

No (test)data on the mixture available

### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	OECD 474		Mouse (male/female)	Bone marrow	Inconclusive, insufficient data

Judgement is based on the relevant ingredients

### Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### Soudal high viscosity super glue

No (test)data on the mixture available

### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral	NOAEL	Carcinogenic toxicity study	42.3 mg/kg bw/day	18 month(s)	Rat (male/female)	No carcinogenic effect		Experimental value

Judgement is based on the relevant ingredients

### Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### Soudal high viscosity super glue

No (test)data on the mixture available

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

7 / 13

# Soudal high viscosity super glue

## 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	OECD 421	50 mg/kg bw/day	40 day(s) - 48 day(s)	Rat	No effect	Foetus	Experimental value
	LOAEL	OECD 421	200 mg/kg bw/day	40 day(s) - 48 day(s)	Rat	Mortality	Foetus	Experimental value
Maternal toxicity	NOAEL	OECD 421	50 mg/kg bw/day	40 day(s) - 48 day(s)	Rat	No effect		Experimental value
	LOAEL	OECD 421	200 mg/kg bw/day	40 day(s) - 48 day(s)	Rat	Reduced body weight and food consumption	General	Experimental value
Effects on fertility	NOAEL	OECD 421	12.5 mg/kg bw/day	50 day(s) - 52 day(s)	Rat (male)	No effect	Male reproductive organ	Experimental value
	LOAEL	OECD 421	50 mg/kg bw/day	50 day(s) - 52 day(s)	Rat (male)	Reproductive performance	Male reproductive organ	Experimental value
	NOAEL	OECD 421	50 mg/kg bw/day	40 day(s) - 48 day(s)	Rat (female)	No effect	Female reproductive organ	Experimental value
	LOAEL	OECD 421	200 mg/kg bw/day	40 day(s) - 48 day(s)	Rat (female)	Reproductive performance	Female reproductive organ	Experimental value

Judgement is based on the relevant ingredients

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Toxicity other effects

#### Soudal high viscosity super glue

No (test)data on the mixture available

### Chronic effects from short and long-term exposure

#### Soudal high viscosity super glue

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Soudal high viscosity super glue

No (test)data on the mixture available

#### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 5 mg/l	96 h	Oryzias latipes	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	> 4.8 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	> 5 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC	OECD 202	0.34 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP
	LOEC	OECD 202	0.89 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC50	OECD 209	> 10000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value

Classification of the mixture is based on the relevant ingredients

### Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

Not classified as dangerous for the environment according to the criteria of Directive 1999/45/EC

### 12.2. Persistence and degradability

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

8 / 13



# Soudal high viscosity super glue

## 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301C: Modified MITI Test (I)	0 %; Oxygen consumption	28 day(s)	Experimental value

### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
SRC AOP v1.92	9.42 h	500000 /cm <sup>3</sup>	Calculated value

### Conclusion

No test data of component(s) available

## 12.3. Bioaccumulative potential

### Soudal high viscosity super glue

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

### ethyl 2-cyanoacrylate

#### Log Kow

Method	Remark	Value	Temperature	Value determination
EU Method A.8		0.776	22 °C	Experimental value

## 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	320 - 840	60 day(s)	Cyprinus carpio	Experimental value

#### Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 107		6.25	20 °C	

### Conclusion

No test data of component(s) available

## 12.4. Mobility in soil

### 6,6'-di-tert-butyl-2,2'-methylene-di-p-cresol

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		5.1625	QSAR
Koc		150000	QSAR

#### Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
7.9 atm m <sup>3</sup> /mol				Calculated value

### Conclusion

No (test) data on mobility of the components available

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Other adverse effects

### Soudal high viscosity super glue

#### Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09\* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

9 / 13

# Soudal high viscosity super glue

Carefully stir with water. Allow waste to solidify. Remove to an authorized dump. Incinerate under surveillance with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into the sewer. Do not discharge into surface water.

## 13.1.3 Packaging/Container

### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

Transport	Not subject
UN number	3334

#### 14.2. UN proper shipping name

Proper shipping name	Aviation regulated liquid, n.o.s.
----------------------	-----------------------------------

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	9
Classification code	M11

#### 14.4. Packing group

Packing group	
Labels	

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	
Limited quantities	

### Rail (RID)

#### 14.1. UN number

Transport	Not subject
UN number	3334

#### 14.2. UN proper shipping name

Proper shipping name	Aviation regulated liquid, n.o.s.
----------------------	-----------------------------------

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	9
Classification code	M11

#### 14.4. Packing group

Packing group	
Labels	

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	
Limited quantities	

### Inland waterways (ADN)

#### 14.1. UN number

Transport	Not subject
UN number	3334

#### 14.2. UN proper shipping name

Proper shipping name	Aviation regulated liquid, n.o.s.
----------------------	-----------------------------------

#### 14.3. Transport hazard class(es)

Class	9
Classification code	M11

#### 14.4. Packing group

Packing group	
Labels	

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	
Limited quantities	

### Sea (IMDG/IMSBC)

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

10 / 13

# Soudal high viscosity super glue

14.1. UN number	Transport	Not subject
	UN number	3334
14.2. UN proper shipping name	Proper shipping name	Aviation regulated liquid, n.o.s.
14.3. Transport hazard class(es)	Class	9
14.4. Packing group	Packing group	
	Labels	
14.5. Environmental hazards	Marine pollutant	-
	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	960
	Limited quantities	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	Annex II of MARPOL 73/78	

## Air (ICAO-TI/IATA-DGR)

14.1. UN number	UN number	3334
14.2. UN proper shipping name	Proper shipping name	Aviation regulated liquid, n.o.s.
14.3. Transport hazard class(es)	Class	9
14.4. Packing group	Packing group	III
	Labels	9
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	A27
	Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
	No data available

#### REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
ethyl 2-cyanoacrylate	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304. 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

11 / 13

# Soudal high viscosity super glue

December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'

## National legislation Belgium

### Soudal high viscosity super glue

No data available

## National legislation The Netherlands

### Soudal high viscosity super glue

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 03
--	---

## National legislation France

### Soudal high viscosity super glue

No data available

## National legislation Germany

### Soudal high viscosity super glue

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

### ethyl 2-cyanoacrylate

TA-Luft	5.2.5
---------	-------

### 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol

TA-Luft	5.2.5; I
---------	----------

## National legislation United Kingdom

### Soudal high viscosity super glue

No data available

## Other relevant data

### Soudal high viscosity super glue

No data available

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H-statements referred to under headings 2 and 3:

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H361f Suspected of damaging fertility.

(\*) INTERNAL CLASSIFICATION BY BIG  
CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)  
DMEL Derived Minimal Effect Level  
DNEL Derived No Effect Level  
EC50 Effect Concentration 50 %  
ErC50 EC50 in terms of reduction of growth rate  
LC50 Lethal Concentration 50 %  
LD50 Lethal Dose 50 %  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
OECD Organisation for Economic Co-operation and Development  
PBT Persistent, Bioaccumulative & Toxic  
PNEC Predicted No Effect Concentration  
STP Sludge Treatment Process  
vPvB very Persistent & very Bioaccumulative

### Specific concentration limits CLP

ethyl 2-cyanoacrylate	C ≥ 10 %	STOT SE 3; H335	CLP Annex VI (ATP 0)
-----------------------	----------	-----------------	----------------------

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption,

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

12 / 13

# Soudal high viscosity super glue

storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

S  
O  
U  
D  
A  
L

Reason for revision: 2;3

Publication date: 2005-10-21

Date of revision: 2017-02-16

Revision number: 0302

Product number: 42864

13 / 13