DANLERS Controls for Lighting & HVAC				
Home	Products	Literature		
Home	DSSGD MK400W (Trade price list	Contact details
Order code: DSSGD MK400W	 Soft start dimmer with slim push button control. To suit MK Grid Plus. Can be used to dim lights from several locations. Suitable for dimming mains and/or dimmable transformer low voltage lamps. Suitable for mains halogen (e.g. GU10) lamps, without the need for derating. Functions Slim button gives an easy press action. Holding the button down dims or brightens the light to any level. A quick press switches off. Another press returns the lamp softly to its previous brightness. Can also be used to control the speed of fans and motors. Restriction: not suitable for fluorescent loads. Special features The soft start feature prolongs the bulb life. This dimmer automatically switches off in the 			
	event of transformer instability, protecting the dimmer and the transformer. Multi-way switching and dimming can be achieved from any position by using the matching slave switches (the SS–SL and SS GS models). The grid module versions fit any position on the appropriate grid or plate system. Specification			
	Min. and max. wattag Resistive, mains hale dimmable electronic transform	ogen or	00W	
	Min. and max. wattag Dimmable wirewoun transformer inductiv	d or toroidal	50W	
	Max. no. of transform	ners: 6		
	Dimensions (mm):	59 x 2	24 x 34	
	Wall box depth (mm):35For loading of Grid dimmers on multi-gang plates, the following limits also apply:			
	2 gang plates:	maximu	m for total plate – 630V	V
	3 or 4 gang plates:	maximu	m for total plate – 1000	W
	6, 8, 9 or 12 gang pla		m per row – 1000W	
	18 or 24 gang plates	: maximu	m per row – 1200W	

