

SMART FLOOD EXTERIOR LIGHTING



- Low Energy Flood Light.
- IP65.
- Integral Photocell Option. (external use only).
- Polycarbonate Case and Diffuser.
- Light Weight.
- Compact & Robust construction.
- Extremely Easy to Install.
- Asymmetric Reflector.
- Hinged Front Facia.
- Available in: Black, White and Titanium finishes.
- Sign Extension Option.

Lamp & Operating options

- 13w – 26w TCD.
- 32w – 42w TCT (high frequency only).
- Switch Start PFC and High frequency operating options.

Designed with a host of installation features

- Brass Inserts.
- Light Weight.
- Mounting Angle Referencing.
- Ratchet System on Bracket.

Wattage	Lumen Output	Tungsten Wattage Equivalent
18w TCD	1200 Lumens	100w
26w TCD	1800 Lumens	150w
32w TCD	2200 Lumens	185w
42w TCD	3200 Lumens	260w

ENERGY SAVING COMPARISON

Based On: Total annual hours of darkness 3,000 hours per annum.

Running cost comparison at 7.5p per KW hour. Over 3,000 hours.



300w Halogen

Lumen Output	4,800 Lumens
Average Rated Life	2,000 Hours



42w Biax

Lumen Output	3,200 Lumens
Average Rated Life	10,000 Hours

COST COMPARISONS

300w Linear Halogen	£ 67.50
42w Biax	£ 9.60

ANNUAL SAVING £ 57.90