

#### **Features**

Wireless portable monitor with large LCD screen
Real time and accumulated consumption
Six tariff settings with independent start time, cost rate
and weekday/weekend selection
Selectable tariff cost currency
Clock, calendar and temperature display

Alarm functions to alert the user when the power exceeds the user setting

PC application allows USB data download for further analysis

Last 30 days "1 minute average current" PC graphs available include:

Live usage (last two minutes) History usage Comparative usage

# **Technical**

Operating frequency 433MHz
Operating range up to 30m
12 second refresh rate
Display battery life > 18 months
Transmitter battery life > 18 months
Sensor suitable to monitor cables rated up to 71A

Storage conditions: -5°C to +60°C

Relative humidity: 25% to 95% non condensing

Operating temperature: 5°C to 45°C Ingress protection: IP30

### **Standards**

IEC 61010-1:2001(2nd Edition) /
EN 61010-1:2001(2nd Edition)
ETSI EN 300 220-1 V2.1.1 (2006-04)/
ETSI EN 300 220-2 V2.1.2 (2007-06)
ETSI EN 301 489-1 V1.8.1 (2008-04)/
ETSI EN 301 489-3 V1.4.1 (2002-08)
R&TTE
WEEE Directive, RoHS, Battery Directive

## **Includes**

LCD display unit
Transmitter unit
Fixed single sensor
USB lead
Software CD
(Windows Operating System)
6 x AA alkaline battery
User manual



2 Save Energy Ltd

The Annexe, Field House Barn Chineham Lane, Sherborne St John Basingstoke, Hants RG24 9LR UK

Tel: +44 1256 383 430 www.theowl.com



# **Screen Views**

....

Cost of current & accumulated electricity consumption display
Power consumption (kW) display
Current consumption (Amps) display
Accumulated energy consumption (kWH) display
Current & accumulated Green house gas (GHG)
emission rate display
Average & Historical displays for all main values

