

# GP Self-regulating cable for Gutters and Downpipes

- Stops accumulation of snow and ice
- Prevents damage to gutters and properties
- Reduces danger from collapsing gutters and falling icicles



Keep gutters and downpipes ice-free

## Applications

- Domestic properties
- Commercial Premises

## Features

- Power consumption decreases as ambient temperature increases
- No chance of hot spots from cables crossing or touching
- Can be cut to length on site
- UV resistant
- Full length earth braid
- Use a single run for gutters up to 120mm wide and an additional run for every extra 120mm
- Cables require 230V supply
- Connection to power lead via a suitable gel filled connector



- Tin coated copper bus wires
- Self limiting polymer with bonded jacket
- Thermoplastic insulation
- Metal braid
- Thermoplastic over jacket

Structure of GP-18 heating cable



FST2-EX  
IP65 Frost  
Thermostat



GC-E gel filled  
push fit end  
seal



GP-S spacer kit

## Cable

Model	W/m
GP-18	18

## Accessories

Model	Description
GC-E	Gel filled end seal
GP-S	Spacer Kit (also protects against sharp edges)

## Optional Control

Type	Description	Model	Details
Thermostat	IP65 Frost thermostat	FST2-EX	Page 72



GP-S spacer protecting GP-18  
cable from a sharp edge

## Cable length against breaker size

Breaker (A)	6	10	16	20
Max Cable length (m)	28	48	76	92