

SWD Industrial Finned Tubular Heaters

- Ideal for damp and corrosive environments
- Suitable for 'hose-down' washing
- Designed for long life in the most demanding conditions



SWD Industrial Finned Tubular Heater ideal for damp and corrosive environments

Features

- Welded stainless steel construction
- Built-in adjustable thermostat (SWD-A models only)
- Brackets for wall or floor mounting supplied as standard
- Waterproof glass fibre terminal box IP66 rated
- M20 cable gland supplied as standard
- Optional zinc plated wire guards available (recommended when personnel have access to the heater)

Heater Range			
Model	kW	Volts	Built-in Thermostat
SWD-A-500	0.5	230V	Yes
SWD-A-1000	1.0	230V	Yes
SWD-A-1500	1.5	230V	Yes
SWD-A-2000	2.0	230V	Yes
SWD-A-3000	3.0	230V	Yes
SWD-U-500	0.5	230V	No
SWD-U-1000	1.0	230V or 400V/3	No
SWD-U-1500	1.5	230V or 400V/3	No
SWD-U-2000	2.0	230V or 400V/3	No
SWD-U-3000	3.0	230V or 400V/3	No
SWD-U-4000	4.0	230V or 400V/3	No
SWD-U-500-1	0.5	110V	No
SWD-U-1000-1	1.0	110V	No
SWD-U-1500-1	1.5	110V	No



SWD-A with externally adjustable thermostat

Heater Technical Data					
kW	Dimensions (mm)			Weight (kg)	Optional Guard
	L	W	H		
0.5	440	130	170	3.0	SWG-1
1.0	640	130	170	4.8	SWG-2
1.5	840	130	170	6.2	SWG-3
2.0	1040	130	170	7.7	SWG-3
3.0	1440	130	170	10.9	SWG-4
4.0	1840	130	170	13.7	SWG-5



SWD-U standard format

Optional Guard Range

Model
SWG-1
SWG-2
SWG-3
SWG-4
SWG-5



SWD mounted under SWG Guard
 An SWD guard is recommended when personnel have access to the heaters

Optional Guard Technical Data

Model	Dimensions (mm)			Weight (kg)
	L	W	H	
SWG-1	450	240	240	1.0
SWG-2	650	240	240	1.5
SWG-3	1075	240	240	2.0
SWG-4	1600	240	240	3.5
SWG-5	1900	240	240	4.0



SWD heaters can be floor mounted or wall mounted using the brackets provided

