

CH2 Ceramic Heaters



RADIANT HEATERS

- Heats people rather than space
- Direct radiant heating without light output
- Virtually instant heat – ideally suited to irregularly used premises

Typical Applications

- Community halls
- Workshops
- Kennels
- Zoos

Features

- Aluminium construction with safety grille
- Long life 'no glow' ceramic heat emitters
- Wall mounting bracket with 'up and down' and 'side to side' angle adjustment
- 1m high temperature cable

Single Ceramic Heaters

Heater Range		
Model	kW	Finish
CH2-15	1.5	Ivory
CH2-15B	1.5	Black

Red print indicates available from stock.
Typical delivery for other models: 5 working days.

Two Ceramic Heaters

Heater Range			
Model	kW	Orientation	Finish
CH2-30	3.0	Vertical	Ivory
CH2-30B	3.0	Vertical	Black
CH2-30L	3.0	Linear	Ivory
CH2-30LB	3.0	Linear	Black

Red print indicates available from stock.
Typical delivery for other models: 5 working days.

Technical Specification					
kW	Volts	Dimensions(mm)			Weight (kg)
		H	W	D	
1.5kW	230	218	375	100	3.2
3kW (Vertical)	230	376	375	100	5.7
3kW (Linear)	230	218	788	100	5.7



CH2-15



CH2-15B



CH2-30



CH2-30B



CH2-30L



CH2-30LB

Control Options

Description		Model	Details
Dimmer (3kW max)		VR-2	Page 78
Push Button Timer (3kW max)		TS-6	Page 75
Push Button Timer (6kW max)		TS-7	Page 75
Movement Sensor (3kW max)		WH-402	Page 78



1.5kW ceramic heater providing warmth in a fisherman's cafe

Ceramic heater keeping a flower seller warm at a London station

