

Product Code: OA502AG

Luckinslive 397504099

Description: 2 Gang IP66 Weatherproof Unfurnished Unit



### General Information

Dimensions (mm)	158 (W) x 158 (H) x 90 (D)		
Accessory Fixing Centres (mm)	120.6		
Colour	Anthracite Grey		
Gasket Colour	Black		
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
Anti Microbial Certified	No		
Maximum Accessory Depth (mm)	35		
Back Box Knockouts - Total (mm)	8 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	2 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	2 x Ø20
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

**Standards** BS 5733, BS EN 60529

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Accepts standard two gang accessory plates.

