GRIDPRO

Technical Specification

CLICK Scolmore GROUP

Product Code: GM2018PW-WD

Description: 20AX Double Pole Switch Module

Luckinslive 405537547





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)		
Colour	Polar White		
Insert Colour	Polar White		
Switch Finish	Polar White		
Materials	Body & Insert: Nylon	Switch: Urea	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass		
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	20		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
Product Marking	Waste Disposal		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

ANTIBACTERIAL & ANTIVIRAL CERTIFIED

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN