GRIDPRO

Technical Specification

CLICK Scolmore GROUP

Product Code: GM2080PW

Description: 240V~ Red Indicator Module

Luckinslive 404478490





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)
Colour	Red
Insert Colour	Polar White
Materials	Body & Insert: Nylon Terminals: Brass
	Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated
Anti Microbial Certified	No
Operating Voltage (AC)	250
Frequency (Hz)	50
Termination Type	Screw
Terminal Size (mm)	Ø5
Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5, 2 x 4
Neon Indicator	Yes
Indicator Colour	Red
Minimum Back Box Depth (mm)	25 (35 Flat Plate)
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN