GRIDPRO

Technical Specification

CLICK Scolmore GROUP

Product Code: GM2218PW-HT

Luckinslive 438513321

Description: 20AX Double Pole Switch With LED Module





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 23.5 (D)		
Colour	Polar White		
Insert Colour	Polar White		
Switch Finish	Polar White		
Materials	Body & Insert: Nylon	Switch: Urea	
	LED Lens: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass PCB Components	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	20		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
LED Indicator	Yes	Indicator Colour	Red
Product Marking	Hot Tap		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

ANTIBACTERIAL & ANTIVIRAL CERTIFIED

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN