GRIDPRO

Technical Specification

CLICK Scolmore GROUP

Product Code: GM2586PW

Luckinslive 437484147

Description: 2.4A Type A & 3A Type C USB Dual Charging Module





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 40 (D)		
Colour	Polar White		
Materials	Front Covers: Nylon	Rear Housing: Nylon	
	Electronics: USB Connections & Cable	Fixing Screws: Nickel Plated Steel	
Anti Microbial Certified	No		
Operating Voltage (AC)	100-240	Frequency (Hz)	50/60
Resistive Load Rating (A)	2.4 & 3		
USB Output Type	USB Type 'A' & Type 'C'		
USB Number Of Outputs	2	USB Charging Total Load (A)	5.4
USB Charging Voltage (V DC)	5	USB Standby Current (W)	<0.1
Termination Type	Screw		
Terminal Size (mm)	1.2		
Terminal Capacity - Solid (mm^2)	3 x 2.5, 2 x 4 or 1 x 6.0		
Product Marking	5V DC 2.4A 5V DC 3A		
Minimum Back Box Depth (mm)	35 (47 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Warranty - Electronics (Years)	2

Standards BS EN 62368-1, BS EN 61000-6-1, BS EN 61000-6-3

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Do not insulation resistance test the circuit with the module installed.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Internally fused which enables direct mains supply.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN