GRIDPRO

# Technical Specification

CLICK Scolmore GROUP

Product Code: GM9001

Luckinslive 404486437

Description: 6A 2 Way Push On/Off (Non-Dimmable) Module



## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 25 (W) x 62 (H) x 22 (D) | | |
| Materials | Body: Nylon | | Terminals: Brass |
| | Terminal Screws: Brass | | PCB: Multiple Electronic Components |
| Operating Voltage (AC) | 230 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 6 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø2.8 | Terminal Torque Value (Nm) | 0.2 |
| Terminal Capacity - Solid ($mm^2$) | 2 x 1.5 | | |
| 2 Way Switch | Yes | | |
| Dimmer Technology Type | None (On & Off Only) | | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 2 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Due to the housing height, the module cannot be mounted directly above another on a multi-tier mounting plate.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN