

Technical Specification

Product Code: VPMB425BK

Description: 10AX Ingot 1 Gang Intermediate Plate Switch



General Information

| | | |
|--|--|--|
| Plate Dimensions (mm) | 88 (W) x 88 (H) x 8 (D) | |
| Dimensions With Gasket (mm) | 91 (W) x 91 (H) x 9 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| MiniGrid Plate (Gang) | 1 | |
| MiniGrid Single Width Module Quantity | 1 | |
| MiniGrid Double Width Module Quantity | 0 | |
| Style | Victorian | |
| Finish | Matt Black | |
| Insert Colour | Black | |
| Gasket Colour | Black | |
| Materials | Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel | Insert: Urea Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Gasket: Nylon |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Inductive Load Rating (AX) | 10 | |
| Load Rating Comments | Suitable for Inductive Loads | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) 0.5 |
| Terminal Capacity - Solid (mm²) | 4 x 1.5 or 2 x 2.5 | |
| Modular Rocker Switches | Yes | |
| Intermediate Switch | Yes | |
| Minimum Back Box Depth (mm) | 16 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Supplied with Matt Black plate fixing screws.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

