

Product Code: CMA796

Luckinslive 438820690

Description: 13A 2 Gang Switched Socket Outlet With Twin Type C USB (4.2A) Outlets



General Information

Plate Dimensions (mm)	146 (W) x 86 (H) x 9,5 (D)	
Plate Fixing Centres - Horizontal (mm)	120,6	
Style	Rounded Profile	
Colour	Polar White	
Materials	Front Plate & Rocker Switch: Urea	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	PCB: Mixed Components	Earth Strap: Mild Steel
Anti Microbial Certified	Yes	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
USB Output Type	USB Type 'C'	
USB Number Of Outputs	2	USB Charging Total Load (A) 4,2
USB Charging Voltage (V DC)	5	USB Standby Current (W) 0,1
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1,2
Terminal Capacity - Solid (mm ²)	3 x 2,5 or 2 x 4	
Single Pole Switched	Yes	
3 Pin Safety Shuttered	Yes	
Twin Earth Terminals	Yes	
Product Marking	5V DC 4,2A (SHARED)	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	25	Warranty - Electronics (Years) 2
Standards	BS 1363-2: 2016 +A1: 2018, EN IEC 62368-1, EN IEC 62368-3, EN IEC 62680-1-3, EN IEC 61000-6-1 & EN 61000-6-3	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Independent Charging: 5V DC, 4.2A - USB Type C (3A), USB Type C (3A)

Intelligent chip incorporated within the USB PCB adjusts the output according to the load connected.

