

Product Code: MCPo20

Technical Specification

Luckinslive 437625456



Description: 10A 3 Pole Fan Isolation Plate Switch



General Information

Dimensions (mm) 88 (W) x 88 (H) x 48 (D)

Plate Fixing Centres - Horizontal (mm)

Style Metal Clad Pro Colour Dusty Grey Polar White Insert Colour

> Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Operating Voltage (AC) Resistive Load Rating (A) 10

> Termination Type Screw

Terminal Size (mm) Ø3.5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

Modular Rocker Switches Triple Pole Switch

Product Marking Isolator, On, Off'

Supplied Back Box Depth (mm)

Back Box Knockouts - Total (mm) 6 x Ø20 Back Box Knockouts - Top (mm) 1 x Ø20

Back Box Knockouts - Left Side (mm) 2 x Ø20 Back Box Knockouts - Rear (mm) 1 x Ø20

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-2-4, BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99,9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com







Insert & Rocker Switch: Urea

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm)

Back Box Knockouts - Bottom (mm) 1 x Ø20

Back Box Knockouts - Right Side (mm) 1 x Ø20

Earth Strap: Mild Steel



