


Product Code: MCPo51BK

## **Technical Specification**

Luckinslive 437625760



LED



Insert, Switch, Fuse Drawer & Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass



## **General Information**

Dimensions (mm)  $88 (W) \times 88 (H) \times 48 (D)$ 

Plate Fixing Centres - Horizontal (mm) 60.3

Style Metal Clad Pro

Colour Black Insert Colour Black

Materials Front Plate & Mounting Box:

Electrophoretically Coated Steel

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Frequency (Hz) 50

Operating Voltage (AC) 25 Resistive Load Rating (A) 13

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) 4.8 × 4.8 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm<sup>2</sup>)  $3 \times 2.5$  or  $2 \times 4$ 

Switched Yes

Double Pole Switch Yes
Twin Earth Terminals Yes

TWIN Earth Terminats Yes

LED Indicator Yes Indicator Colour Red

Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Supplied Back Box Depth (mm) 40

Back Box Knockouts - Total (mm) 6 x Ø20

Back Box Knockouts - Top (mm) $1 \times \emptyset 20$ Back Box Knockouts - Bottom (mm) $1 \times \emptyset 20$ Back Box Knockouts - Left Side (mm) $2 \times \emptyset 20$ Back Box Knockouts - Right Side (mm) $1 \times \emptyset 20$ 

Back Box Knockouts - Rear (mm) 1 x Ø20 Back Box Earth Terminal Supplied Yes

Terminal Supplied Yes Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com









