

Product Code: MCP201PW

Luckinslive 437624240

Description: 50A 1 Gang Double Pole Plate Switch With LED



General Information

| | | |
|--|--|--|
| Dimensions (mm) | 88 (W) x 88 (H) x 58 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Metal Clad Pro | |
| Colour | Polar White | |
| Insert Colour | Polar White | |
| Materials | Front Plate & Mounting Box: Electrophoretically Coated Steel LED Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass | Insert, Switch & Rear Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 50 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø6.5 | Terminal Torque Value (Nm) 2.5 |
| Terminal Capacity - Solid (mm²) | 1 x 16 | |
| Double Pole Switch | Yes | |
| Twin Earth Terminals | Yes | |
| LED Indicator | Yes | Indicator Colour Red |
| Product Marking | On & Off | |
| Supplied Back Box Depth (mm) | 50 | |
| Back Box Knockouts - Total (mm) | 6 x Ø20 | |
| Back Box Knockouts - Top (mm) | 1 x Ø20 | Back Box Knockouts - Bottom (mm) 1 x Ø20 |
| Back Box Knockouts - Left Side (mm) | 2 x Ø20 | Back Box Knockouts - Right Side (mm) 1 x Ø20 |
| Back Box Knockouts - Rear (mm) | 1 x Ø20 | |
| Back Box Earth Terminal Supplied | Yes | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 20 | |

Standards BS EN 60669-1

Additional Information

LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

