

Product Code: MCP536PW

Luckinslive 437624907

Description: 13A 2 Gang Double Pole Switched Socket Outlet



General Information

|                                        |                                                                 |                                              |
|----------------------------------------|-----------------------------------------------------------------|----------------------------------------------|
| Dimensions (mm)                        | 148 (W) x 88 (H) x 48 (D)                                       |                                              |
| Plate Fixing Centres - Horizontal (mm) | 120.6                                                           |                                              |
| Style                                  | Metal Clad Pro                                                  |                                              |
| Colour                                 | Polar White                                                     |                                              |
| Insert Colour                          | Polar White                                                     |                                              |
| Materials                              | Front Plate & Mounting Box:<br>Electrophoretically Coated Steel | Insert & Rocker Switch: Urea                 |
|                                        | Rear Housing: Urea                                              | Terminals: Brass                             |
|                                        | Terminal Screws: Steel & Yellow Passivated                      | Contacts: Silver "on-lay" Copper / Brass     |
|                                        | Internal Busbars: Formed Pressed Brass                          | Earth Strap: Mild Steel                      |
| Operating Voltage (AC)                 | 250                                                             | Frequency (Hz) 50                            |
| Resistive Load Rating (A)              | 13                                                              |                                              |
| Termination Type                       | Screw                                                           |                                              |
| Terminal Size (mm)                     | Ø5                                                              | Terminal Torque Value (Nm) 2                 |
| Terminal Capacity - Solid (mm²)        | 3 x 2.5 or 2 x 4                                                |                                              |
| Double Pole Switch                     | Yes                                                             |                                              |
| 3 Pin Safety Shuttered                 | Yes                                                             |                                              |
| Twin Earth Terminals                   | Yes                                                             |                                              |
| Supplied Back Box Depth (mm)           | 40                                                              |                                              |
| Back Box Knockouts - Total (mm)        | 8 x Ø20                                                         | Back Box Knockouts - Bottom (mm) 3 x Ø20     |
| Back Box Knockouts - Top (mm)          | 2 x Ø20                                                         | Back Box Knockouts - Right Side (mm) 1 x Ø20 |
| Back Box Knockouts - Left Side (mm)    | 1 x Ø20                                                         |                                              |
| Back Box Knockouts - Rear (mm)         | 1 x Ø20                                                         |                                              |
| Back Box Earth Terminal Supplied       | Yes                                                             |                                              |
| Ingress Protection                     | IP20                                                            |                                              |
| Operational Temperature (°C)           | -5 to +40                                                       |                                              |
| Warranty (Years)                       | 20                                                              |                                              |

Standards BS 1363-2

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

