

Product Code: MDg001

Luckinslive 389103754

Description: 6A 2 Way Push On/Off (Non-Dimming) Module



General Information

Dimensions (mm)	25.5 (W) x 67 (H) x 23.2 (D)	
Materials	Body: Nylon	Terminals: Brass
	Terminal Screws: Brass	PCB: Multiple Electronic Components
Operating Voltage (AC)	230	Frequency (Hz) 50
Resistive Load Rating (A)	6	
Termination Type	Screw	
Terminal Size (mm)	Ø2.8	Terminal Torque Value (Nm) 0.2
Terminal Capacity - Solid (mm²)	2 x 1.5	
2 Way Switch	Yes	
Dimmer Technology Type	None (On & Off Only)	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	2	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Due to the housing height, the module cannot be mounted directly above another on a multi-tier mounting plate.

