

- Made from high-grade virgin polyurethane to provide outstanding tear & shear strength, and also exceptional abrasion, tensile and compression stress resistances (superior to PVC or recycled rubber alternatives)
- All lengths can be simply joined by interlocking male:female connectors
- Can accept all vehicular traffic (UK max 11.5t Axle Weight)
- All 3 and 5 cavity versions have solid bases with compartmentalised channels, and toughened-hinged lids. Suitable for armoured cables, hoses and pipes
  - Single cavity option simply lays over cables. Ideal for flexes and arctic-grade cables up to 12mm diameter
- End Caps can provide perfect finish
- · Carrying handle on reverse side
- Produced in UK
- Longevity of use enables exceptional value

Code	Dimensions (LxWxH)	Cavity Sizes	Colour	Axle Weight
DO-1B765 EC-1B765	765 x 133 x 22mm End Cap Pair for DO-1B76	1x 38x12mm 5	Black	12.0t
	920 x 460 x 35mm End Cap Pair for DO-3BR92	3x 64x18mm 20	Black Lid, Red Base	12.4t
DX-5RB910	910 x 505 x 45mm	4x 34x30mm 1x 41x30mm	Red Lid, Black Base	15.3t
EC-5RB910	End Cap Pair for DX-5RB910			
	910 x 473 x 75mm End Cap Pair for DX-3RB91	3x 53x52mm LO	Red Lid Black Base	17.6t









