

CXL Combination Storage Heaters

CXL 12 / CXL 18 / CXL 24



Product Description

thermostatically controlled convector.

Storage heater with manual input charge control and

- Key Features
- All the features and benefits of XL range
- Manually adjustable input charge regulator
- Room temperature boost control
- Separate thermostatically controlled convector, providing silent top up heating when required
- Frontal grille for efficient heat distribution
- Suitable for domestic or commercial use

Technical Specification

Storage: Charge input, room temp boost Convector: On/off, room temp thermostat

Storage Core

High density bonded magnetite bricks

Storage Elements

0.85 kW

Convector Element

Stitched ribbon

Insulation

Front and rear: microporous silica Top and ends: resin-free mineral wool Base: calcium silicate slab

Input Charge Controller

Bi-metal.

Thermal Cut Out

Bimetal, manual reset

Damper Control (Boost)

Bi-metal strip

Room Temperature Thermostat

Hydraulic, manually adjustable

Colour/Finish

Front and side panels: Willow White Grille and wall spacer: Birch Grey


Cable Length

None fitted

Standard Warranty

12 months

Product Range Details



CXL12

CXL18

CXL24

	OALIZ	OALIO	UNLLT
Performance			
Input rating	1.70 kW	2.55 kW	3.4kW
Charge acceptance (7hr)	11.9 kW	17.85 kW	23.8 kW
No Elements (0.85kW)	2	3	4
Max Convector Output	0.9 kW	1.45 kW	2.0 kW
Other convector outputs*	0.45 kW	0.45/1.0	0.65/1.3
Dimensions			
Height (A)	706mm	706mm	706mm
Width (B)	565mm	793mm	1021mm
Depth (C)	193mm	193mm	193mm
Weight (incl. bricks)	77kg	111kg	146kg
Packed weight	19.5 kg	24 kg	29.5 kg

Additional Information

Storage Bricks - Packed separately in pairs approx. weight 7.5kg each

† - When using Dimplex shelves a clearance of 150mm must be maintained

Accessories

XL9050 – Tamper proof kit (storage controls) XL9001 – Tamper proof kit (convector controls)

XL8924 - Convector inhibitor resistor

SHE12/18/24 - Storage Heater Shelves

* Selectable on installation