

Girona Panel Heater (White) - Series C



Technical Details

recriffical Details								
Controls	Digitally controlled, Electronic Thermostat accurate to (±0.2°C). Set- point range (7-30°C) Timer modes: 7 Day Programmable User Timer, Out All Day, Home All							
	Day							
	Continuous heat modes: Eco, Manual, Frost Protect. Additional modes: Away, Boost, Setback, Runback							
Controller UI	Graphical display with RGB backlight							
	Capacitive buttons with audio feedback							
	User replaceable battery (Coin-Type)							
Controller Functions	Open window detection							
	Adaptive-start,							
	Advance time period							
	Bluetooth for software updates							
	Child Lock & Heater Lock (PIN-based)							
Construction	Durable epoxy-polyester powder coated steel casing with louvered upward facing grille							
	Advanced controls with cap-sense technology for total flexibility of heating							
Element	Compact, finned, mineral filled sheathed element							
Installation	1 H-frame wall bracket for easy fixing							
Safety	Thermal cut-out. Auto reset type							
	Overheat detection							
IP Rating	IP24							
Battery Backup	1 x CR2032 Lithium Manganese Dioxide 3V coin cell battery to backup real time clock (weight 3g). Battery life > 5 years.							
Supply	1.3 metres fitted, 3 core for fused spur installation, 1/N/PE ~230-240 V, 50Hz Class I, with earth wire							
Colour / Finish	Metal Chassis, Air Outlet Grille & Control Moulding - Traffic White (RAL 9016)							

Warranty & Approvals

Approvals	UKCA, CE, BEAB
Warranty	2 Years
Country of Origin	United Kingdom
Manufacturer	Glen Dimplex Heating & Ventilation (GDC Group Ltd)

Product Description


GFPWE features intuitive user controls, allowing the programming of multiple 7-day timer profiles via a backlit LCD display and capacitive buttons

Key Features

- Modern panel design with louvered upward facing grille for optimum heat circulation
- Customisable heating with four time and temperature settings per day.
- Adaptive start pre-heating and open window detection auto-shutdown
- Slimline design that covers traditional panel heater fixing marks
- Aesthetics to compliment storage heater ranges
- Smartphone app controllable via the Dimplex Control system*

*Requires additional hardware, sold separately. A Dimplex Hub and RFM 'Radio Frequency Module' device are required for this product to connect to the Dimplex Control system and be controlled via the Dimplex Control smartphone app

Dimensions



								facing top right side only			
Model/Item No.(EAN- Code 5011139+Item No.)	090850	GFP050WE	090867	GFP075WE	090874	GFP100WE	090881	GFP150WE	090898	GFP200WE	
Output (kW)	0.50		0.75		1.00		1.50		2.00		
Height 'D' (mm)	565		565		565		565		565		
Width 'C' (mm)	530		530		700		770		940		
Depth 'E' (mm)	107		107		107		107		107		
Weight (Kg)	13.4		13.4		16.9		18.6		22.1		
		Pack	aging	Detail	s						
Height (mm)	670		670		670		670		670		
Width (mm)	590		590		764		837		1000		
Depth (mm)	182		182		182		182		18	32	
Packed Weight (Kg)	15.1		15.1		19		20.7		24	.4	
Ti	10		10		7		7		ε	5	
Hi	3		3		2		2		2	2	
Pallet Quantity (2.4m high)	30		30		14		14		1	2	