

Girona Panel Heater (Black)



Technical Details

Controls	Digitally controlled, Electronic Thermostat accurate to ($\pm 0.2^{\circ}\text{C}$) Timer modes: 7 Day Programmable User Timer, Out All Day, Home All Day, Holiday Continuous heat modes: Eco, Manual, Frost Protect, Setback, Runback, Off
Controller UI	<ul style="list-style-type: none"> Graphical display with RGB backlight Capacitive buttons with audio feedback User replaceable battery (Coin-Type)
Controller Functions	<ul style="list-style-type: none"> Open window detection, Adaptive-start, Advance time period Adjustable max SP range ($7-32^{\circ}\text{C}$) Bluetooth for software updates Child Lock & Landlord Lock (PIN-based)
Construction	Durable epoxy-polyester powder coated steel casing with louvered upward facing grille Advanced controls with cap-sense technology for total flexibility of heating
Element	Compact, finned, mineral filled sheathed element
Installation	1 H-frame wall bracket for easy fixing
Safety	<ul style="list-style-type: none"> Thermal cut-out. Auto reset type Overheat detection
IP Rating	IP24
Battery Backup	3.3V coin cell battery to backup real time clock. Battery life > 5 years.
Supply	1.3 metres fitted, 3 core for fused spur installation, 1/N/PE ~230-240 V, 50Hz Class I, with earth wire
Colour / Finish	Metal Chassis, Air Outlet Grille & Control Moulding - Traffic White (RAL 9016)

Warranty & Approvals

Approvals	CE, BEAB
Warranty	2 Years
Country of Origin	United Kingdom
Manufacturer	Glen Dimplex Heating & Ventilation (GDC Group Ltd)


Product Description

GFPBE features intuitive user controls, allowing the programming of multiple 7-day timer profiles via a backlit LCD display and capacitive buttons

Key Features

- Elegant designer panel with upwards facing grille for optimum heat circulation
- Intuitive user controls with RGB backlit LCD display
- User programmable room temperatures with multiple seven-day timer profiles
- Electronic thermostat accurate to within 0.2°C
- Energy-saving technologies such as Adaptive Start and Open Window Detection
- Aesthetics to compliment storage heater ranges
- Splash proof for use in bathrooms
- Complies with Lot 20 of ERP Directive

Dimensions



Model/Item No. (EAN-Code 5011139+Item No.)	090904	GFP050BE	090911	GFP075BE	090928	GFP100BE	090935	GFP150BE	090942	GFP200BE
Output (kW)	0.50		0.75		1.00		1.50		2.00	
Height 'D' (mm)	565		565		565		565		565	
Width 'C' (mm)	530		530		700		770		940	
Depth 'E' (mm)	107		107		107		107		107	
Weight (Kg)	13.4		13.4		16.9		18.6		22.1	
Packaging Details										
Height (mm)	670		670		670		670		670	
Width (mm)	590		590		764		837		1000	
Depth (mm)	182		182		182		182		182	
Packed Weight (Kg)	15.1		15.1		19		20.7		24.4	
Ti	10		10		7		7		6	
Hi	3		3		2		2		2	
Pallet Quantity (2.4m high)	30		30		14		14		12	