

Four Channel Day/Night CCTV system with integral digital recording



- Day/Night cameras with LED illumination
- Digital full screen recording
- Built in on-screen motion detection
- Up to 16 weeks continuous recording
- Compatible with CCTV monitor or standard TV
- Cameras suitable for indoor or outdoor use
- USB output for captured image transfer
- Quad or single screen view



DAY

NIGHT





BUSINESS



ELITE SECURITY PRODUCTS

HOME



DIGI-VIEW[4]

Four Channel Day/Night CCTV system with integral digital recording

DIGI-VIEW[4] offers a comprehensive digital CCTV solution for home or business use. The cameras, suitable for exterior or interior use without any additional housing, offer clear colour images during the day and crisp infra red illuminated mono images at night. Also included in the system is a high capacity digital video recorder which allows simple control, recording and viewing of images whilst also providing power for the cameras. To complete the system a cable is included for direct connection to a standard televison or an optional dedicated CCTV TFT monitor.

DIGI-VIEW[4] offers the user many recording options in order to optimise the 160Gb of record space available, there is even built in motion detection which looks for movement on screen, without need for additional equipment, to trigger a record session.

Camera Specification

Description	1/4"Colour Day & Night Infrared Camera		
Pick up Element	SHARP 1/4" CCD Image Sensor		
Number of Pixels	<ntsc> 510(H) x 492(V) <pal> 500(H) x 582(V)</pal></ntsc>		
Back Light Compensation	ON		
Auto Electronics Shutter	ON		
AGC	ON		
Sync Mode	Internal Sync		
Scanning System	2:1 Interlace		
Auto White Balance	ON		
Resolution	420 TV Lines		
S/N Ratio	> 48 dB		
Gamma	0.45		
Minimum illumination	0.92 Lux. F /2.0 (0 Lux with IR)		
Horizontal Sync Frequency	<pal> 28.3 KHz</pal>		
Video Output	1.0Vp.p. 75ohm		
Power Source	DC 12V (Supplied from DVR)		
Water Resistance	IP66		
IR LED	10PCS		
Night Viewable Range	5-8 meters		
Power Consumption	350mA max		
Operating Temperature	-10°C to + 60°C		
Lens	3.6mm lens		
Shutter Control	<pal> 1/50-1/110,000 sec</pal>		
Dimension	52 (D) x 75 (H) mm		
Net Weight	0.6kg		

DVR Specification

Description 4 channel stand alone DVR					
Hard drive	Fixed - Internal 160GB Seagate IDE				
Video input format	PAL				
Video input	4 channel composite				
Video output	4 channel composite				
Power output	350ma 12VDC each channel				
Motion detection	Selectable - Sensitivity adjustable				
Alarm input	4 selectable no/nc				
Alarm outputs	1 selectable				
Alarm buzzer	Yes				
Display frame rate	100 frames per second				
Record frame rate	Max 25 frames per second adjustable				
Record quality	Adjustable - high, medium, low				
Recording modes	Continuous, motion, manual, scheduled				
Display resolution	720 × 576				
Recording resolution	320 × 136, 640 × 272				
Compression format	Modified mpeg 12 - 20 k bytes / frame				
Search facility	Time - date - camera				

DVR Record Times (160GB hard drive)

DISPLAY FORMAT	QUALITY	25FPS	12FPS	6FPS	1FPS
EACH SCREEN	HIGH	64HRS	128HRS	256HRS	1536HRS
	NORMAL	92HRS	184HRS	368HRS	2208HRS
	LOW	116HRS	232HRS	464HRS	2784HRS
QUAD SCREEN	HIGH	116HRS	232HRS	464HRS	2784HRS
	NORMAL	172HRS	344HRS	688HRS	4128HRS
	LOW	256HRS	452HRS	904HRS	5424HRS



Optional Extras

TFT15 - 15" LCD monitor TFT17 - 17" LCD monitor CAB-20 - 20m camera extension cable CAB-COUP cable coupler

Be the best install the best...

Electronics Line UK Ltd

Unit 7, Leviss Trading Estate, Station Road, Stechford, Birmingham B33 9AE. Tel: 0121 789 8111 Fax: 0121 789 8055 Technical Support: 0121 7861 881 E-mail: info@espuk.com Website: www.espuk.com

