

IR-DOME

Internal use Day / Night Dome Camera

Features

- Integral LED Illumination (10m)
- Colour in Day – Mono in darkness
- Fixed 4mm Lens
- 420TVL Horizontal resolution

IMAGE SENSOR	1/3" Color SONY CCD
EFFECTIVE PIXELS	PAL: 500(H)×582(V) /NTSC: 510(H)×492(V)
SIGNAL SYSTEM	PAL/NTSC
RESOLUTION	420TVL
MINIMUM ILLUMINATION	0.2Lux/F2.0, 0Lux(IR On)
LENS	Board Lens 4mm
S/N RATIO	More than 48dB(AGC OFF)
EXPOSURE MODE	EE
ELECTRONIC SHUTTER SPEED	PAL:1/50- 1/100,000 (sec) NTSC: 1/60 – 1/100,000 (sec)
GAMMA	0.45
WHITE BALANCE	ATM
AGC GAIN CONTROL	Auto
DAY & NIGHT	Auto
SYNC SYSTEM	Internal
INFRARED LUMINARY	24 pcs ϕ 5 IR-LED
ILLUMINATION DISTANCE	10m
VIDEO OUTPUT	1.0Vp-p,75Ohms
POWER REQUIREMENT	DC12V
POWER CONSUMPTION	120mA(IR OFF),350±5%mA(IR ON)
OPERATION TEMP	-10°C —50°C
DIMENSION	95mm(ϕ)×85mm(H)
WEIGHT	Approx 170g
MATERIAL	Plastic