

IRCAM1000

External use Varifocal Day / Night Bullet Camera

Features

- Integral LED Illumination (50m)
- Colour in Day - Mono in darkness
- Varifocal Manual 5 to 50mm Lens
- 560TVL Horizontal Resolution

Signal System	PAL
Effective Pixels	752(H) x 582(V)
Image sensor	1/3" SONY Super HAD CCD
Shutter Speed	1/50(1/60) ~ 1/120,000 SEC
Video Output	1.0Vp-p,75Ω
Scanning Frequency	Horizontal: 15.62KHz / Vertical: 50Hz
Scanning System	2:1 interlace / internal
Horizontal Resolution	560 TV Lines
Minimum Illumination	0.00006(LUX) /0.00LUX(inIR Mode)
Gamma Correction	0.45
S/N Ratio	More than ≥ 50dB (AGC OFF)
White Balance	Automatic White Balance
AGC	ON
BLC	ON
IR Capability	15 pcs ϕ 5 IR-LED
IR Illumination Distance	50m
Operating Temp:	-10~50℃
Water Resistance	IP 66
Lens	5 to 50mm Manual Varifocal
Dimensions (cms)	97(ϕ) x 200 (L)
Weight (kgs)	2
Power Source	DC12V
Power Consumption	800mA max