

IRCAM900

Features

- Integral LED Illumination (50m)
- Colour in Day - Mono in darkness
- Varifocal Manual 6 to 50mm lens
- 480TVL Horizontal Resolution
- Cable Management Bracket

Signal System	PAL
Effective Pixels	752(H) x 582(V)
Image sensor	1/3" SONY Super HAD CCD
Sensing Area	4.9mm x 3.7mm
Shutter Speed	1/50(1/60) ~ 1/100,000 SEC
Video Output	1.0Vp-p, 75Ω
Scanning Frequency	Horizontal 15.625KHz / Vertical: 50 Hz
Scanning System	2:1 interlace / internal
Horizontal Resolution	480 TV Lines
Minimum Illumination	0.2Lux (F1.2)/ 0LUX (in IR mode)
Gamma Correction	0.45
S/N Ratio	≥ 50dB (AGC OFF)
White Balance	Automatic White Balance
AGC	ON
BLC	ON
IR Capability	36 pcs ϕ 8 IR-LED
IR Illumination Distance	More than 50m
Operating Temp:	-10~50°C
Water Resistance	IP 66
Lens	6 to 50mm Manual Varifocal
Dimensions (cms)	
Weight (kgs)	
Power Source	DC12V
Power Consumption	120mA (IR OFF), 500mA (IR ON)