

INTEGRA

CCTV Monitor with integrated DVR



INTEGRA 4

4 Channel Monitor and DVR System



INTEGRA 8

8 Channel Monitor and DVR System

Integra offers a compact attractive CCTV solution by combining the latest DVR technology with a high quality TFT display. An intelligent user interface and advanced network and remote viewing capability makes Integra the right choice in even the most demanding applications.

SYSTEM

- Triplex operation (record, view live, view remotely at the same time)
- Full remote viewing capability via fixed or dynamic IP address
- Password protection
- iPhone, Android remote viewing via APP
- E-mail alert of trigger events
- Integral PTZ with most popular protocols
- Complete with remote control

RECORDING

- Record all cameras in full screen all the time
- Search recordings by event or specified time and date
- Integral 500GB hard drive
- Record by schedule / event / on-screen motion or external trigger
- Back up of recorded data to USB stick or external R/W CD
- Up to eight channels of audio

DISPLAY

- 15" TFT monitor
- View in single channel, quad or multi screen mode
- Monitor standby facility
- Separate control of brightness and contrast
- Separate control of colour on each channel

RECORDING OPTIONS



SCHEDULE AND CONTINUOUS



ALARM



MOTION

VIEWING OPTIONS



MOBILE



LOCAL NETWORK



REMOTE VIEWING



VGA OUTPUT



MOUSE CONTROL



USB BACK UP



Remote viewing with Mobileye APP for iPhone and Android



www.espuk.com

INTEGRA 4

4 Channel Monitor and DVR System



INTEGRA 8

8 Channel Monitor and DVR System



TECHNICAL SPECIFICATION

	INTEGRA 4	INTEGRA 8
Video Format	PAL	PAL
Video Format	H.264 Baseline Compression	H.264 Baseline Compression
Video Input	BNC 4 Input / 1 Output	BNC 8 Input / 1 Output
Audio Format	G.726 8Kx16bit ADPCM Mono	G.726 8Kx16bit ADPCM Mono
Audio Input	RCA 4 Input / 1 Output	RCA 8 Input / 1 Output
Alarm Type	Motion detection, Sensor Input, Relay Output, Video Loss	Motion detection, Sensor Input, Relay Output, Video Loss
Sensor In/Out	4CH Input / 1CH Output	4CH Input / 1CH Output
Display Frame Rate	Each Channel PAL 25 FPS, NTSC 30 FPS	Each Channel PAL 25 FPS, NTSC 30 FPS
LCD Monitor	15" Color LCD, 1024x768, 4:3, 450:1, 150nit, CCFL	15" Color LCD, 1024x768, 4:3, 450:1, 150nit, CCFL
Playback Resolution (CH1)	25fps/(CIF) 25fps/(halfD1), 12fps/D1	25fps/(CIF) 12.5fps/(halfD1), 6.25fps/D1
Record Frame Rate	100FPS@CIF, 100FPS@halfD1, 50FPS@D1	200FPS@CIF, 100FPS@halfD1, 50FPS@D1
Record method	Power-on Auto Record, Scheduled Record (Manual Record, Motion Detection, Sensor Trigger) Support Privacy Mask	Power-on Auto Record, Scheduled Record (Manual Record, Motion Detection, Sensor Trigger) Support Privacy Mask
HDD Interface	SATA Interface support 1000GB	SATA Interface support 1000GB
Network Protocol	TCP-IP/ DHCP / DNNS / PPPoE / E-Mail	TCP-IP/ DHCP / DNNS / PPPoE / E-Mail
Network Function	IE Browser Live Monitor, Configuration, Download Video Mobile Phone Surveillance	IE Browser Live Monitor, Configuration, Download Video Mobile Phone Surveillance
USB 2.0 Interface	Mouse / Portable Mobile HDD/ Flash Drive/ DVD Burner/ Firmware Upgrade	Mouse / Portable Mobile HDD/ Flash Drive/ DVD Burner/ Firmware Upgrade
Playback Method	Normal Play, Fast Forward, Rewind, Single Step	Normal Play, Fast Forward, Rewind, Single Step
Network Interface	RJ45 10M/ 100M Ethernet Auto Detect	RJ45 10M/ 100M Ethernet Auto Detect
PTZ Protocol	PELCO-P, PELCO-D	PELCO-P, PELCO-D
Video Backup	AVI	AVI
Power Adapter	DC 12V Adapter	DC 12V Adapter
Power Consumption	10~15W	10~15W
Operating Temperature	0~+40	0~+40
Operating Humidity	10%~90% RH	10%~90% RH
Dimensions	360 x 360 x 160mm (WHD) inc. stand/base	360 x 360 x 160mm (WHD) inc. stand/base

Elite Security Products
Unit 7, Target Park, Shawbank Road
Lakeside, Redditch B98 8YN



Telephone: 01527 515150
Technical Support: 01527 515145
email: info@espuk.com