

SPYCAM

Internal use Board camera

Features

- Fixed 3.6mm FULL or PINHOLE lens
- 380TVL Horizontal resolution (SONY board)
- For Covert Surveillance applications

Signal	PAL
Effective Pixels	500(H) x 582(V)
Image sensor	1/3" SONY Super HAD CCD
Sensing Area	4.9mm x 3.7mm
Shutter Speed	1/50(1/60) ~ 1/100,000 SEC
Video Output	1.0Vp-p,75Ω
Scanning Frequency	Horizontal: 15.625KHz / Vertical: 50Hz
Scanning System	2:1 interlace / internal
Horizontal Resolution	420 TV Lines
Minimum Illumination	0.1LUX (F1.2)/0 LUX (in IR mode)
Gamma Correction	0.45
S/N Ratio	≥ 48dB (AGC OFF)
White Balance	Automatic White Balance
AGC	ON
BLC	ON
IR Illumination Distance	More than 15m
Operating Temp:	-10~50°C
Water Resistance	IP 66
Lens	3.6mm/F2.0
Option Pinhole Lens	3.7mm/F2.0
Dimensions (cms)	3.8(L)x3.8(W)
Weight (kgs)	0.02
Power Source	DC12V
Power Consumption	120mA