



Single Way IP Video Door Entry

Product Code: A1IPDSM1

Description: Aperta IP PoE Multi Way Outdoor Station HD with Proximity Reader



General Information		Supply & Power	
Dimensions (r	nm) 365 x 140 x 50	Operating Voltage (V	DC) 15
Fir	ish Brushed Silver	Secondary Power So	rce PoE 802.3af/at
Mater	ials Aluminium Alloy	Power Consumption (nA) <150
Moun	ing Surface & Flush	Lock out	put 12VDC, NO & NC Contacts
Fob Reader Operating Freque	ncy 13.56MHz	Network	
Fobs Suppo	ted 200	Network Rate (Mbps)	10/100/1000 Mbps Self-adaptive
Warranty (Ye	ars) 3		Ethernet
Media Information			
Camera	1.0MP CMOS Low Illumination	_	
Screen Size (Inches)	4.3" Colour TFT LCD		
Video Compression	H.264		
Viewing Angle (°)	90 (Horizontal)		
Audio	Noise Suppression & Echo Cancellation	 	
Programming			
User Interaction	Keypad & GUI via LCD Screen	_	
PIN Length	6		
Environment			
Ingress Protection	IP65	_	
Impact Rating (IK)	10		
Operating Temperature (°C)	-10 to +50		
Relative Humidity Resistance (%)	< 90		

Supplied Weather Shield & Mounting Casing, 4 x Double Terminal Blocks, 1 x Triple Terminal Block, 7 core Cable (1m), 4 core cable (1.0m), Screw & Rawl plug pack, Foam Gasket, Quick Start Guide

Features Built-in Keypad & Fob reader for unlocking door Audio message alerts user if the door has been unlocked. Accessories

A1IPT10: Aperta IP 13.56MHz Pack of 10 Tags

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com



Errors ecification is subject t