

Product Code: MAG2P

Description: 2 Zone ABS Conventional Fire Panel



General Information

Dimensions	340mm x 290mm x 100mm
Max Detectors Per Zone	20
Thresholds for Zone Conditions	0 - 2 mA (Fault condition) 2 - 6 mA (Normal condition) 6 - 110 mA (Fire condition)
Call Points Per Zone	Unlimited
Weight	2.1kg (without battery)

Outputs

Sounder 1	24V (max 300mA fused)
Sounder 2	24V (max 300mA fused)
Fault/Fire Relay	Volt free 500mA @ 24V (max load)
Auxiliary Output	24VDC (300mA fused)

Power

Mains Fail Consumption	50mA
Mains Supply	230 VAC ± 10%
Standby Supply	Up to 12V 7Ah (Battery Calculation Required)
Power Availability	0.7 amps

Environment

Relative Humidity Resistance	(93±3)% @ 40°C
Storage Temperature	-20°C to 60°C
Operating Temperature	-5°C to +40°C

Additional Features

- Integral sound alarm button
- Enable/disable security key
- One man walk test facility
- Individual sounder circuit fault ID
- Individual zone/sounder isolate
- Class change' facility

Accessories

BAT7	12V 7Ah SLA Battery
MAGBAR2/4	Key & Barrel set