

Product Code: MAGPRO96

Description: Addressable 96 Zone Fire Panel



General Information

Dimensions (Metal Casing)	441mm x 331mm x 80mm
Protocol Type	Custom (Closed)
Zones	16 Per Loop
Loops	Up To 4
Maximum Number of events in Log	10240
Wire Gauge	Up to 1.5mm
Weight	6kg

Inputs

Max Devices per Loop	Up to 250 Devices (Loop Calculation Required)
Maximum number of Loops	Expandable up to 2

Outputs

Monitored Outputs	4
Dimensions (Front Cover)	461mm x 344mm x 45mm
Un-Monitored Outputs	4 (240VAC @ 10A)
Auxiliary Output	24VDC @ 300mA

Power

Operating Voltage	230 VAC ± 10% 50/60Hz
PSU Output	7A
Standby Supply	Up to 12V 17Ah (Battery Calculation Required)

Environment

Operating Temperature	-5°C to 50°C
------------------------------	--------------

Accessories

MAGDUOPK	Pack of 2 Keys
BAT18	12V 17Ah SLA Battery
MAGPRO-PROG	Address Programming Tool For MAGPRO Devices
MAGPRO96-L250	Single Loop Expander for 250 Devices
MAGPRO-NIC	Network Interface Card

Components Supplied

- 2 x 10k Ohm Resistors
- 1 x 2A Quick-Blow Fuse