

Technical Specification

Product Code: HC528FDG

Description: 2.8mm Fixed Lens HDview Dome Camera - Grey







Dimensions (mm)	111 x 111 x 95	Recording Storage Type Micro SD, up to 256 GB		
Finish		Environment		
Materials	Metal & Plastic	Ingress Protection	IP67	
Weight (Kg)		Operating Temperature (°C)		
Warranty (Years)		Storage Temperature (°C)		
Supply & Power		Storage Temperature (C)	-30 (0 +33	
Operating Voltage (V DC)	12	_		
Power Consumption (W)				
Other Power Sources	PoE (IEEE802.3af)			
Media Information	,			
Effective Pix	cels 2880 x 1620 (5MP)			
	(") 1/2.7" Progressive CMOS			
Lens size (n				
,	ype Fixed			
Viewing Angle	e (°) 101.1 (H), 55.3 (V), 111.1 (D)			
Auto Electronic Shutter				
Speed (se	c/°) 1 to 1/100000	1 to 1/100000		
Scanning Syst	em Progressive Scan CMOS	Progressive Scan CMOS		
Shutter Speed (F	PS) 30 FPS @ 5MP (2880 x 1620)	30 FPS @ 5MP (2880 x 1620)		
Maximum IR Distance	(M) 30	30		
IR Wavelength (r	nm) 850	850		
Video Bit F	ate 128 Kbps - 16 Mbps	128 Kbps - 16 Mbps		
Microphone Suppor	ted Built-in			
Speaker Suppor	ted Built-in			
White Light Range	(M) 30	30		
Day/Ni	ght IR-Cut filter with Auto Switch (IR-Cut filter with Auto Switch (ICR)		
Basic Detect	tion Motion Detection, Tampering	Motion Detection, Tampering Alarm, Audio Detection		
Intelligent Detect	Support False Alarm Filtering, Line Crossing Detection, Intrusion Detection, Region Entrance Detection Region Exit Detection			
Reset I	Key No			
Network				
Interfa	ace 1 RJ45; 10/100M Base-TX Eth	nernet		
	ant Yes; Profile S, Profile G, Profile	' '		
	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH			
Supplied Quick Sta	rt Guide, Mounting Guide, Installat	ion Screws and Rawlplugs and Pass Throu	igh Gland	
Compatible Products Compatible	le with the range of 24/7 Network \	/ideo Recorders (NVR) 4, 8, 16, 32 and 64	Channels	
Accessories				

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom T: +44 (0)1527 515150 | F: +44 (0)1527 515143

E: info@espuk.com | W: espuk.com







