

Product Code: HC864R48TB

Description: 64 Channel HD 48TB Network Video Recorder (NVR)



General Information

| | |
|------------------|----------------|
| Dimensions (mm) | 426 x 442 x 89 |
| Weight (Kg) | <5.7 |
| Warranty (Years) | 3 |

Supply & Power

| | |
|--------------------------|------------|
| Operating Voltage (V AC) | 100 to 240 |
| Power Consumption (W) | <25 |

Inputs & Outputs

| | |
|-----------------------------|-----------------------------|
| Serial Ports | 1 x RS232, 1 x RS485 |
| Alarm Inputs | 16 |
| Alarm Outputs | 4 |
| Video Input Channels | 64 |
| Audio Output Channels (RCA) | 1 |
| PoE Standards | IEEE 802.3at & IEEE 802.3af |

Media Information

| | |
|----------------------|--|
| Display Video Output | 1 x VGA, 2 x HDMI (HDMI Audio is not supported) |
| Display Split | 1, 4, 6, 8, 9, 16, 25 & 36 (VGA) 1, 4, 6, 8, 9, 16, 25, 36 & 64 (HDMI) |
| Display Resolutions | HDMI1/HDMI2: 4K (3840x2160)(30Hz), 1920x1080p(60Hz), 1920x1080p(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz) VGA: 1920x1080p(60Hz), 1920x1080p(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz) |
| Sync Playback | 16 Channel |
| Data | RS485 |

Network

| | |
|--------------------|--|
| Network Connection | 2 RJ45 10M, 100M, 1000M self-adaptive Ethernet Interface |
| Network Functions | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS |
| USB Interface | 2 x USB (2.0), 1 x USB (3.0) |

- Supplied**
- USB Mouse
 - Quickstart Guide
 - C13 Mains Cable
 - Server Mounting Brackets & Screws x 2
 - Auxiliary Terminal Block x 4

Compatible Products Compatible with the range of 24/7 HDview 5MP and 8MP and Rekor IP 2MP Fixed Bullet and Dome Cameras

Accessories

- IPIN1POE: 1 Channel POE Injector
- IPSW4POE: 4 Channel POE Switch
- IPSW8POE: 8 Channel POE Switch

