

## **Technical Specification**

Product Code: RC228FBG

**Description:** 2.8mm Fixed Lens IP Bullet Camera - Grey







Dimensions (mm) 7	5 x 74 x 191	Storage Type Micro	Recording Storage Type Micro SD, up to 128GB	
Finish G		Environment		
Materials N	Metal	Ingress Protection	IP67	
Weight (Kg) 0	.41	Operating Temperature (°C)		
Warranty (Years) 3		Storage Temperature (°C)		
Supply & Power		Storage remperature ( e)	00 10 1 00	
Operating Voltage (V DC)	12			
Power Consumption (W)	<9			
Other Power Sources	PoE (IEEE802.3af)			
Media Information				
Effective Pixe	els 1920 x 1080			
Sensor Size	(") 1/2.8" Progressive CMOS			
Lens size (m	.,			
•	rpe Fixed			
Viewing Angle	(°) 106.7 (H), 57.1 (V), 115.7 (D)			
Auto Electronic Shutter	(s) Auto / Manual			
Speed (sec	c/°) 1 to 1/100000			
Scanning System Progressive Scan CMOS				
Shutter Speed (FF	<b>PS)</b> 30 FPS @ 1080p	30 FPS @ 1080p		
Maximum IR Distance (	<b>(M)</b> 30			
IR Wavelength (n	<b>m)</b> 850	850		
Video Bit Ra	ate 128 Kbps - 6 Mbps	· · ·		
Microphone Support				
Speaker Support				
White Light Range (				
, · · · · · · · · · · · · · · · · · · ·	ght R-Cut filter with Auto Switch (IC	/ /		
	,	Cross line, Intrusion(based on human body detection), Motion Detection, Tampering Alarm, Audio Detection		
Reset K	(ey No			
Network				
Interfa	ce 1 RJ45; 10/100M Base-TX Ethe	1 RJ45; 10/100M Base-TX Ethernet		
ONVIF Complia	ant Yes; Profile S, Profile G, Profile	Yes; Profile S, Profile G, Profile T		
Network Functio	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS SMTP, SSL, SNMP			
<b>Supplied</b> Quick Star	t Guide, Mounting Guide, Installatio	n Screws and Rawlplugs and Pass Throu	igh Gland	
Compatible Products Compatible	e with the range of 24/7 Network Vid	deo Recorders (NVR) 4, 8, 16, 32 and 64	Channels	
Accessories				
PPC1: UDV/IEW/ID 04/7 Pullet Doop Poo	- 0			

BBG1: HDVIEW IP 24/7 Bullet Deep Base - Grey









