

Product Code: H512VBG

Description: HDview IP PoE Varifocal 2.8-12mm Motorised Lens Bullet Camera Grey



### General Information

Dimensions (mm)	73 x 73 x 206
Finish	Grey & Black
Materials	Graphene & Metal
Mounting	Surface
Weight (Kg)	0.51
Warranty (Years)	3

### Recording

Storage Type	Micro SD, up to 256 GB
--------------	------------------------

### Environment

Ingress Protection	IP67
--------------------	------

### Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	9.6
Other Power Sources	PoE (IEEE802.3af)

### Media Information

Effective Pixels	2880 x 1620 (5MP)
Sensor Size (")	1/2.7" Progressive CMOS
Lens size (mm)	2.8-12
Lens Type	Varifocal (Motorised)
Viewing Angle (°)	96.4 - 32.7
Electronic Shutter Type	Auto / Manual
Speed (sec/°)	1 to 1/100000
Scanning System	Progressive Scan CMOS
Frames Per Second (FPS)	5MP (2880*1620), Max 25fps 4MP (2560*1440), Max 25fps 3MP (2304*1296), Max 30fps 1080P (1920*1080), Max 30fps
Maximum IR Distance (m)	40
IR Wavelength (nm)	850
Video Bit Rate	128 Kbps - 6 Mbps
Microphone Supported	Built-in
Day/Night	IR-Cut filter with Auto Switch (ICR)
Basic Detection	Cross line, intrusion(based on human body detection), Motion Detection, Ultra Motion Detection, Tampering alarm, Audio Detection
Intelligent Detection	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP authentication

### Network

Interface	1 RJ45; 10/100M Base-TX Ethernet
ONVIF Compliant	Yes; Profile S, Profile G, Profile T
Network Functions	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP,SSL/TLS

**Supplied** Quick Start Guide, Mounting Guide, Installation Screws and Rawlplugs and Pass Through Gland

**Compatible Products** Compatible with the range of 24/7 Network Video Recorders (NVR) 4, 8, 16, 32 and 64 Channels

### Accessories

BBG1: HDVIEW IP 24/7 Bullet Deep Base - Grey

