

Product Code: ECSPST

Description: Smart Thermostat & Receiver



Supplied

- Fort Smart Thermostat
- Fort Smart Receiver
- Thermostat Stand
- Receiver Mains Adapter
- Receiver Flylead Adapter
- Receiver Mains Bulkhead
- Installation Pack
- QuickStart Guide
- 2 x AA batteries

Component 1

Thermostat

Quantity

1

Component 2

Receiver

Quantity

1

General Information

Dimensions (mm)	100 x 100 x 22
Finish	White
Materials	Polycarbonate
Mounting	Wall or Desk Mounted

Supply & Power

Operating Voltage (V DC)	3
Battery Type	AA (LR06) x 2
Output Relay Rating	8A @ 250V AC
Output Type	Normally Open or Normally Closed
Battery Low Indicator	Yes
EE Class	ErP Class IV

Programming

Adjustment Type	3 Buttons; Up, Down, ON/OFF
Programming Type	App Based
Programming Schedule	7 Day, 5/2 Day and 5/1/1 Day
Set Temperature Range (°C)	5 to 35
Temperature Display Range (°C)	0 to 50
Modes Available	Manual, Schedule & Boost

Transmission

Transmission Frequency (MHz)	868
Maximum Communication Range (m)	100

Environment

Frost Protection	Yes (5°C)
Ingress Protection	IP21
Operating Temperature (°C)	0 to +50

Warranty Years 1

Features

- Key Lock Facility
- Low Battery Indication
- Frost Protection
- Alexa & Google Assistant Integration
- ClickSmartPlus App Integration
- Optional Intelligent Function "Optimal Start"
- Open Window Detection
- Touch Buttons
- Permanent User & Program settings during power loss

General Information

Dimensions (mm)	86 x 86 x 28.5
Finish	White
Mounting	Surface

Router Transmission Frequency (GHz) 2.4

Wireless Range - Open Field (m) 100

Supply Voltage (V AC) 100 - 240

Frequency (Hz) 50

Connection Type Flylead or Mains Plug

Output Relay Rating 8A @ 250V AC

Output Type Selectable:
Normally Open & Common
Normally Closed & Common

IEC Protection Class II

EE Class ErP Class IV

Adjustment Type Single Button

Optimisation Optimum Start

Ingress Protection IP21

Operating Temperature (°C) 0 to +50

