

ESPIRE

Product Code: ES1MODRF

Description: Input Module Powered by a 10 Year Battery

Technical
Specification
Accessories

ESP
ScolmoreGROUP



General Information

Dimensions (mm)	86 x 86 x 54 (Backbox Included)
Colour	White
Materials	Urea
Mounting	Single Pattress – Surface and Flush Mounting (backbox included)
Indication	2 LEDs; Green & Red
Weight (Kg)	0.2

Supply, Power & Backup

Supply Type	Battery Powered
Operating Voltage (V DC)	3
Cable Size (mm ²)	0.75 - 2.5
Relay/Contact Type	Volt-free Normally Open Short to trigger
Battery Backup	Non-replaceable 10 Year Battery
Battery Type	3V Lithium
Battery Size	CR17450
Battery Chemistry	Lithium
Battery Lifetime	10 Year

Interconnectability

RF-LINK Supported	Built-in
RF-LINK Frequency (MHz)	868.3
RF-LINK Range (Open Field)(m)	100
Maximum Supported Wired & RF-LINK Interconnected Devices	28

Environment

Operating Temperature (°C)	0 to +40
Relative Humidity Resistance (%)	95 (non-condensing)

Compatible Products RF-Link supported Espire Products

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuke.com | **W:** espuke.com



CLICK OR SCAN

Catalogue



DoC



Installation



CLICK OR SCAN