

STANLEY®



MULTI DIRECTIONAL WORKLIGHTS

50W MULTI DIRECTIONAL WORKLIGHT

Key Features

- Three power modes (100%, 50%, off): The worklight can be adjusted to different brightness levels according to the user's needs
- 360 Degree folding heads allowing light for any direction: The heads of the worklight can be rotated in any direction, providing illumination in all angles
- Frosted shatterproof lens: The worklight is equipped with a frosted lens that is resistant to shattering, ensuring durability and safety
- Freestanding base included
- Tripod mountable using Stanley universal tripod code: SXLS37627E: The worklight can be mounted on a tripod using the specified Stanley universal tripod code, providing additional flexibility in positioning See page 13
- 220-240v 50/60 Hz: The worklight operates on mains power with a voltage range of 220-240v and a frequency of 50/60 Hz
- Die cast aluminium housing: The worklight is housed in a durable die cast aluminium casing, ensuring longevity and protection
- IP54: The worklight has an IP54 rating, indicating that it is protected against dust and water splashes, making it suitable for use in various environments
- Cable Type : H05RN-F 3G1.0mm2
- Cable Length : 1.5 meters



Stanley universal tripod.
See page 13

Code	Description	Colour Temp	Lumens	IP Rating	Dimensions
SXLS37180E	50w mains powered multi directional worklight	6000K	4500	IP54	L405 x W190 x H300mm

2 X 30W MAINS POWERED WORKLIGHT

Key Features

- Aluminium frame with moulded rubber grip: The worklight has an aluminium frame with a moulded rubber grip, providing a comfortable and secure hold during use
- 360 Degree rotating heads allowing light for any direction: The heads of the worklight can be rotated 360 degrees, allowing for versatile lighting in any direction
- Frosted shatterproof lens: The worklight is equipped with a frosted lens that is resistant to shattering, ensuring durability and safety
- Freestanding base included
- Tripod mountable using Stanley universal tripod code: SXLS37627E: The worklight can be mounted on a tripod using the specified Stanley universal tripod code, providing additional flexibility in positioning See page 13
- 220-240v 50/60 Hz
- Die cast aluminium housing
- Cable Type : H05RN-F 3G1.0mm2
- Cable Length : 2 meters



Stanley universal tripod.
See page 13

Code	Description	Colour Temp	Lumens	IP Rating	Dimensions
SXLS37951E	2 x 20w mains powered worklight	4000K	3200	IP44	L175 x W485 x H315mm