

TP&N Switch Disconnector

3 Pole and Neutral isolators for safe and effective power disconnection from 32A to 125A (AC-23A rating). Our isolators are housed in large, robust 1.2mm IP65 steel enclosures, complete with removable gland plates at the top and bottom for a flexible installation. A red/yellow door interlock handle provides clear ON/OFF indication. The door is mechanically interlocked when in the 'ON' position and can be padlocked when switched 'OFF'. Designed for electricians, our signature spacious interior makes wiring fast and frustration-free.

Compatible with our Main Switch and TPN consumer units.



- AC-23A: 32A, 63A, 80A, 100A, and 125A options to suit commercial and industrial installations.
- Large, durable 1.2mm steel enclosure with a powder-coated RAL7035 finish.
- Manually operated red/yellow handle for secure ON/OFF isolation.
- Mechanically interlocked door in the 'ON' position to prevent access.
- Handle can be padlocked in the OFF position for extra-secure isolation (max. 3 padlocks).
- Removable gland plates at the top and bottom
- Spacious internal layout ensures easy cable termination.
- Operating temperature range of -25°C to +55°C.

Product Code	Description
TPNI032	32A ISOLATOR 3P+N
TPNI063	63A ISOLATOR 3P+N
TPNI080	80A ISOLATOR 3P+N
TPNI100	100A ISOLATOR 3P+N
TPNI125	125A ISOLATOR 3P+N



IP65



Up to 125A

