

L430S

Wireless Motion Sensor (IP54) – White

Enjoy added peace of mind with the L430S Wireless motion sensor. It's waterproof so you can place it outdoors by your garage or driveway, and by linking it to your Honeywell doorbell kit, you'll always know when a visitor is arriving at your door.



Pack Contents:

1 x Wireless Motion Sensor, 1 x Quick Start Guide, 1 x Safety & Guarantee, 1 x Declaration of Conformity,

Key Features and Benefits:

Early Alerts - This external wireless motion sensor provides a simple and effective way to notify you that a visitor is arriving before they even reach your door. Enabled by Honeywell ActivLink™, the sensor connects with your Honeywell doorbell to trigger an early alert sound.

Easy To Install - All Honeywell push buttons and accessories are easy to install, with optional screw-free installation and an easy open battery compartment so you can be set up in minutes. All this is backed up by our 2 year product guarantee.

Specification:

| Wireless Motion Sensor | |
|---|-----------------------------|
| Colour | White |
| Wall mounted option | Yes |
| Frequency | 868MHz |
| Wireless Range (m)* | 150 |
| Batteries Included | Yes |
| Low Battery Indicator | Yes |
| Battery Specification | 1 x 9V PP3 (6LR61) |
| Battery Life (Years) | 1 |
| Operating Temperature/Storage Temperature | 0°C to +40°C/-20°C to +60°C |
| Detection Range (m) | 12 |
| Detection Angle (degrees) | 105 |
| Test Mode | Yes |
| Tamper Protection | Yes |
| Sticky Pads | Yes |
| Battery Specification | 1 x 9V PP3 (6LR61) |
| Battery Life (Years) | 1 |

| | |
|------------------------------|-------------------------------------|
| IP Rating | IP54 |
| Detection Range (m) | 12 |
| Detection Angle (degrees) | 140 |
| Dimensions (mm) / Weight (g) | 111 (h) x 73 (w) x 93 (d) / 152 (g) |
| Fixings | Screws / Rawl Plugs |

Pack

| | |
|-----------------------------------|--------------------------------------|
| EAN Code | 5004100967411 |
| Pack Dimensions (mm) / Weight (g) | 140 (h) x 115 (w) x 90 (d) / 238 (g) |
| Standard Pack Quantity | 4 |

* Measured in open field conditions, walls, ceilings and metal structures will reduce the maximum range.