Taps

Non-Concussive, Single Level Mixer, Automatic Infrared





Usage

This range of taps is ideal for use with Hyco Rho and Aquila instantaneous water heaters to provide optimum handwashing performance in washroom settings and for use with Hyco Speedflow and Powerflow water heaters.


Features and Benefits

- Sprayhead range of taps all with removable M22/M24 nozzles
- Reduce water consumption by up to 50% compared to traditional taps by controlling the flow rate
- Save energy by up to 50% compared to traditional taps by reducing the amount of hot water required per handwash
- Where the taps are used with a Speedflow or Powerflow water heater an optional thermostatic mixing valve is recommended (see page 40)
- Hyco Rho and Aquila instantaneous water heaters are only intended for use with spray head taps of this type.
 If traditional taps which do not control the water flow rate are used then optimum performance will not be achieved.
- All taps supplied complete with a choice of three tap spray nozzles – 2.0, 2.5 or 3.0 l/m
- Other flow rates available on request

Product Code	Description	Reach (mm)
TAPNC	Non-concussive tap	150
TAPSLM	Single lever mixer tap	160
TAPIFR	Automatic touch free tap	150

Tap Spray Nozzle Options

Product Code	Max Flow Rate (l/m)	Best suited to water heater	Colour Code Identification
IN-TSN-2.0	2.0	4.4 kW Rho	White/Black
IN-TSN-2.5	2.5	6.0 kW Rho	White/Green
IN-TSN-3.0	3.0	9.6 kW Rho	White/Lilac



Non-Concussive Tap

Simple 'push tap' operation.
Tap functions for a period of time and then closes automatically.
Prevents vandalism and continuous running and saves water.
Use for hot or cold water – blue and red identification rings supplied with each tap.
WRAS approved



Simple manual operation by lifting the control lever up and down. Rotating the control lever clockwise or anti-clockwise reduces or increases the mixed water temperature.

Automatic Infrared (Touch Free) Tap Hygienic no touch automatic

operation.

Dual mains or battery powered

operation.

Complete with cable for connection to the power supply. Usage timer prevents vandalism and continuous running and saves water.

Mixer lever gives option to dispense hot and cold water if required.

WRAS approved

Standard Warranty

1 year parts or replacement warranty for all tap models.







Product Code	Height (mm)	Diameter (mm)	Reach (mm)	Weight (kg)
TAPNC	140	50	150	0.8
TAPSLM	160	50	160	1.0
TAPIFR	140	50	150	1.7