

ARC DOWNLIGHTS (mains halogen reflector lamps)

D1026, D1027, D626

- APPLICATIONS**
- Ideal for highlighting in retail, leisure and commercial applications, particularly where the illumination of vertical surfaces is important.

SALES FEATURES

- COMPREHENSIVE RANGE**
- Two sizes (145mm and 183mm diameter); white, black or silver-grey finish.
- QUALITY**
- Fully adjustable: 65° pivot, 355° rotation (D626, 60° pivot).
 - PTFE-coated lamp leads.
 - F-marked: suitable for direct mounting on flammable surfaces.
 - Guaranteed for five years.
- EASE OF INSTALLATION & MAINTENANCE**
- Tension springs provide quick and positive fixing and allow easy removal for maintenance and decoration.
 - Front ring pulls down for easy lamp change.
 - Supplied with 600mm flying lead.
 - Comprehensive instructions.
- MAINS-VOLTAGE HALOGEN REFLECTOR LAMPS (non-dichroic)**
- Crisp, sparkling, white light.
 - Excellent colour rendering.
 - Dimmable with standard mains dimmer.
 - Longer lamp life than standard incandescent lamps.

TECHNICAL SPECIFICATION

MATERIALS

- Bezel rim - Diecast aluminium
- Housing - Diecast aluminium
- Adjustment rod - Zinc-plated steel
- Lampholder - LCP
- Wiring - PTFE coated
- Fixing springs - Zinc-plated, tempered-spring steel
- Finish - Powder-coated

TECHNICAL DATA

- Input voltage - 240V
- Running current - 50W 0.2A
75W 0.3A
- Dimming - Suitable for use with standard dimmer
- Weight - 0.47 - 0.9kg
- IP rating - IP20

LAMP DATA

Type	Cap	Watts	Beam Angle	Life (h)
PAR 16	GU10	50	25°	2000
PAR 16	GU10	50	50°	2000
Hi-Spot ES63	GU10	75	25°	2000
Hi-Spot ES63	GU10	75	50°	2000
Hi-Spot ES111	GU10	75	24°	2000

All the above are non-dichroic