



Model 65

Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Helps to reduce the amount of waste that goes to landfill sites

Features

- 20% quieter than standard Model 45
- 1-stage grind technology
- Auto-reverse grinding action
- High-torque Dura-Drive™ induction motor
- Built-in air switch in chrome and brushed steel
- 4 Year guarantee
- Stainless steel grind elements
- Continuous feed
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation


Sample Specification

Food waste disposer(s) shall be InSinkErator® Model 65 with 1-stage grind technology, .65 hp motor, auto-reverse grind system, stainless steel grind elements and built-in air switch with chrome and brushed steel options.

Guarantee: 4 Year parts and service.

The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

Dimensions (mm)



Model 65			
A	318	D	185
B	168	E	131
C	64		

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

Specifications

Type of Feed	Continuous
On/Off Control	Wall Switch or Built-In Air Switch
Motor	Single Phase
Reversing	Auto-Reverse Grind System
Time Rating	Intermittent
Lubrication	Permanently Lubricated Upper & Lower Bearings
Shipping Weight (Approx.)	8.2 kg
Overall Height	318 mm

Grind Technology	1-Stage Grind Technology
Sound Technology	Quiet Sink Baffle Sound Insulation
Grind Chamber Capacity	980 ml
Motor Protection	Manual Reset Overload
Average Water Usage	5 Litres Per Household Each Day
Average Electrical Usage	2-3 kWh per Annum
Drain Connection	1-1/2" (3.81 cm)
Dishwasher Drain Connection	Yes

Volts/Hz	HP	RPM	Average Load
120V, 60 Hz	.65	1725	8.1 A
220-240V, 50 Hz	.65	1425	405 W
220-240V, 60 Hz	.65	1725	405 W

InSinkErator Division
 Suite 6, Building 6
 Hatters Lane
 Croxley Green Business Park
 Watford HERTS WD18 8YH
 United Kingdom
 Sales Tel: (0) 1 923 297 880
 Service Tel: (0) 800 389 3715
 www.insinkerator.co.uk
 EX471-09B-45-35

InSinkErator Division
 Emerson Electric Co.
 4700 21st Street
 Racine, WI 53406-5093 USA
 Sales/Service Tel: 262-554-3652
 www.insinkerator.com/worldmap.html



The Emerson logo is a trademark and a service mark of Emerson Electric Co. InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

©2010 InSinkErator, InSinkErator® is a division of Emerson Electric Co. All Rights Reserved.