

## 230V LED LINKABLE STRIPLIGHT



| MLA part code:                                   | UCLED4   | UCLED9             | UCLED13   | UCLED18             | UCLED22             |
|--|--|--------------------|---|---------------------|---------------------|
| <b>Description:</b>                              | Linear Ultra-Thin switchable LED Strip Lights                                      |                    |   |                     |                     |
| <b>ErP Class:</b>                                | A++  | A+                 | A   | A+                  | A                   |
| <b>Weight (kg):</b>                              | 0.1  | 0.15               | 0.22  | 0.28                | 0.35                |
| <b>Wattage (W):</b>                              | 4  | 9                  | 13  | 18                  | 22                  |
| <b>Lumens (lm):</b>                              | 360  | 760                | 1020  | 1550                | 1730                |
| <b>Efficacy (lm/W):</b>                          | 80   | 85                 | 78  | 83                  | 78                  |
| <b>Power Factor:</b>                             | 0.52   | 0.52               | 0.54  | 0.52                | 0.54                |
| <b>Beam Angle (°):</b>                           | 140  |                    |   |                     |                     |
| <b>Overall dimensions (mm):</b>                  | 280(l) 25(w) 35(p)   | 540(l) 25(w) 35(p) | 840(l) 25(w) 35(p)                              | 1140(l) 25(w) 35(p) | 1440(l) 25(w) 35(p) |
| <b>CCT:</b>                                      | 4000K  |                    |   |                     |                     |
| <b>LED Colours:</b>                              | Cool White   |                    |   |                     |                     |
| <b>CRI:</b>                                      | >80  |                    |   |                     |                     |
| <b>LED type:</b>                                 | SMD  |                    |   |                     |                     |
| <b>Running current (A):</b>                      | 0.036  | 0.073              | 0.11  | 0.15                | 0.18                |
| <b>Input voltage:</b>                            | Mains 230V 50Hz  |                    |   |                     |                     |
| <b>Construction:</b>                             | Polycarbonate  |                    |   |                     |                     |
| <b>Class:</b>                                    | Class II   |                    |   |                     |                     |
| <b>IP rating:</b>                                | IP20   |                    |   |                     |                     |
| <b>Warranty:</b>                                 | 3 Year   |                    |   |                     |                     |
| <b>Supplied with:</b>                            | 2m of cable with connector and 2 mounting clips                                    |                    | 2m of cable with connector and 3 mounting clips |                     |                     |
| <b>Additional Accessories available:</b>         | Link cable 250mm (UC250)<br>Link cable 500mm (UC500)<br>Link cable 1000mm (UC1000) |                    |   |                     |                     |
| <b>Photometric data:</b>                         | Yes  |                    |   |                     |                     |
| <b>Dimmable:</b>                                 | No   |                    |   |                     |                     |
| <b>Instruction sheet:</b>                        | Yes  |                    |   |                     |                     |
| <b>Origin of Manufacture:</b>                    | China  |                    |   |                     |                     |
| <b>Quality assurance system:</b>                 | ISO9001  |                    |   |                     |                     |
| <b>Declaration of Conformity (held on file):</b> | Yes  |                    |   |                     |                     |
| <b>Manufactured &amp; accordance with:</b>       | EN60598  |                    |   |                     |                     |

