



FIRE & CO ALARM CONTROL SWITCH

MODEL RTHL

ALLOWS REMOTE TESTING AND SILENCING
OF HARDWIRED INTERCONNECTED KIDDE
SMOKE, HEAT & CO ALARMS



Overview & Key Features

- Test and Hush Kidde hardwired alarms from a central, easy to reach location
- Red and blue LEDs clearly indicate the type of alarm that has sounded so that appropriate action can be taken
- Connect to any convenient point in a new or existing Kidde hardwire alarm installation
- Multifunction button
 - Test – All interconnected alarms in the system will sound an alarm
 - Hush/Locate – Silence all alarms in the system except the initiating device
- Direct replacement of REMTH

Technical Specifications

General

Order Code:	RTHL
Compatibility:	Kidde and FIREX hard-wired smoke, heat and CO alarms
Power:	230 VAC, 50 Hz, 19 W
Operating Temperature Range:	0 °C to +40 °C
Operating Humidity Range:	Up to 93% RH (non-condensing)
Storage and Transport:	-20 °C to +50 °C, 5% to 95% RH (non-condensing)
Mounting:	BS 4662 1-gang. Minimum depth 25 mm
Number of Interconnected devices:	24 devices (of which 18 can be initiating)

Weights and Dimensions

Unit Dimensions (H,W,D):	86 mm x 86 mm x 10 mm*
Unit Weight (excluding packaging):	75 g
Case Quantity:	6 units

*10mm protrudes from the wall when the unit is installed in wall back box

Compliance



Warranty

10 years